Carmen

ESPECIFICACIONES TÉCNICAS / TECHNICAL SPECIFICATIONS

ARTÍCULO / ARTICLE	TEJIDO / TISSUE		
COMPOSICION / COMPOSITION	95% Polyester 5% Nylon / 95% Pes. 5% Nylon		
	MÉTODO DE ENSAYO / TESTING METHOD	VALOR / VALUE	
PESO / WEIGHT	MÉTODO INTERNO / INTERNAL METHOD	365	gsm2
ANCHO / WIDTH	MÉTODO INTERNO / INTERNAL METHOD	145	cm
SOLIDEZ AL FROTE / FASTNESS TO RUBBING	MÉTODO INTERNO / INTERNAL METHOD	4-5	ciclos
RESISTENCIA A LA ABRASIÓN / ABRASSION RESISTANCE	MÉTODO INTERNO / INTERNAL METHOD	40.000	ciclos
PILLING / PEELING	MÉTODO INTERNO / INTERNAL METHOD	4-5	grados

LIMPIEZA Y CUIDADO / CLEANING AND CARE

Máx. 30º C / 30ª C Max. — No usar lejía / Do not Bleach — Max. 100º C / 110ª C Max. — No Secado / No Drying — Lavado en seco delicado / Delicated dry waxh

1. Informamos que el color de las telas puede variar ligeramente de las muestras de los catálogos.
2. Los resultados de las fichas técnicas son obtenidos por diversas muestras, por tanto la presentación de valores es una media de dichos valores.
3. Suministros LOMAR no asume ninguna responsabilidad por cualquier daño causado por un uso inapropiado, limpieza o daños adicionales.
4. La migración de los colorantes en los textiles con colores intensos y oscuros a brillante es natural e inevitable.
5. Los daños mecánicos no están sujetos a reclamación alguna.

1. We inform, that coloring of fabrics can imperceptibly run away from simples places in catalogues.
2. Test results were received by various samples and therefore presenting average indicative values.
3. LOMAR does not take any responsibility for any damage caused by inappropiate use, cleaning or additional damage.
4. The migration of textile dyes with intense colors and dark to bright is natural and inevitable.
5. Mechanical damage is not subject to complaint.

Pol. Ind. Los Molares nº 5, 02650 Montealegre del Castillo, Albacete, España.

www.morpisofas.es